

60° Gloss Meter DGM60



Introduction

DGM60 gloss meter features with 60° angle, manufactured according to ISO2813. It is also compatible with the standards of ASTM D523, ASTM D2457. DGM60 conforms to corresponding with CIE 1931(2°) under CIE C light source. DGM60 gloss meter can test material with gloss (0-1000Gu), and universally apply to paint, ink, stoving varnish, coating, wood products; marble, granite, vitrified polished le, pottery brick and porcelain; plastic, paper; hardware industries, etc. for gloss measurement and gloss data transmission.

Features

- 60° angle for semi gloss
- Display 5 sets of measurement data, good for comparison
- Connuous mode to check uniformity over large areas
- Connect to PC, more extend functions
- Input gloss value manually
- Large touch screen operation, easy to use
- Beauty appearance, good man-machine communication interface
- Powerful functions to meet many different requirements
- Built-in lithium ion rechargeable battery

Specification

| Item | DGM60 |
|----------------------------|---|
| Measuring Angle | 60° Comply with standard ISO 2813, ASTMD 523, ASTM D 2457 |
| Measuring Area(mm) | 9x15 |
| Measuring Range | 0~1000GU |
| Division Value | 0.1GU |
| Measurement Range | 0-10GU 10-100GU 100-1000GU |
| Repeatability | ± 0.1GU ± 0.2GU ± 0.2%GU |
| Reproducibility | ± 0.2GU ± 0.5GU ± 0.5%GU |
| Chromaticity Corresponding | Corresponding with CIE 1931(2°) under CIE C light source |
| Errors | ±1.2 , ± 1.2% |
| Measuring Time | 0.5s |
| Dimension | L*W*H : 160mm*75mm*90mm |
| Weight | 350g |
| Battery | 3200mAh Li-ion Battery, >10000 times (within 8 hours) |
| Viewing Screen | TFT 3.5 inch, capacitive touch screen |
| Interface | USB/RS-232 |
| Data Save | Basic mode: 1000, Statistical Mode: 5000, Continuous mode: 5000 |
| Software | GQC6 Quality Control Software with QC report printing functions and |
| | more extended functions. |

Specification

| Operation Temperature | 0~40°C (32~104°F) |
|-----------------------|--|
| Storage Temperature | -20~50°C (-4~122°F) |
| Humidity | <85% relative humidity, no condensation |
| Standard Accessories | Power Adapter, USB cable, User Manual, CD (Including QC software), |
| | Calibration Plate |
| Optional Accessories | Miniature Printer |