

STALWART

Ultrasonic Cleaner Industrial S Series



Features

- Welded cleaning tank made of 2 mm stainless steel SUS304/316L tank.
- Drip-proof housing made of stainless steel SUS 304, acid-proof and anti-corrosive
- Industrial grade for 12 hours continuous working
- Inclined tank bottom, for improved cleaning results through ideal distribution of ultrasound.
- It also facilitates the cleaning of the tank. Caking of residues is avoided.
- Multi-direction castors with brake
- Ultrasonic power can be adjusted from 0 to 100%
- Heating can be used non-stop independent of the cleaning.
- Including Stainless steel 304 basket and take-off lid.
- Adjustable Heating
- Handle
- Drain
- Lid/Basket
- Stainless Steel

Specification

Model	Tank Size (mm)	Overall Size (mm)	Volume (L)	Adjustable Heating	Handle	Drain	Lid/Basket
S-36S	500x300x250	1040x770x970	36L	30-110 °C	Y	Y	Y
S-57S	500x350x360	1040x820x1080	57L	30-110 °C	Y	Y	Y
S-96S	600x400x400	1140x870x1120	96L	30-110 °C	Y	Y	Y
S-117S	650x450x400	1190x920x1120	117L	30-110 °C	Y	Y	Y
S-157S	700x500x450	1280x970x1170	157L	30-110 °C	Y	Y	Y
S-206S	750x550x500	1330x1120x1220	206L	30-110 °C	Y	Y	Y