

STALWART

Biological Indicator Incubator SBI-101



Introduction

Biological Indicator Incubator is supporting equipment for bio-indicator. It is small size, light weight, and is suitable for pressure steam sterilizer biological indicator, ethylene oxide sterilization biological indicator, and other biological indicator sterilization effect detection and cultivation.

Features

- Unique designed. Small size, light weight, portable, and suit on various occasions.
- LCD display. Temperature and time display simultaneously.
- Auto fault detect and buzzer alarm. Temperature calibration function.
- 24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.
- Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.
- Timing function. Time range from 1 to 999min.

Specification

Item	SBI-101
Temp. Control Range	R.T. +5°C~100°C
Temp. Setting Range	5°C~100°C
Temp. Stability@56°C	±0.5°C
Temp. Display Accuracy	0.1°C
Heating Speed	<6min (20°C to 56°C)
Time Range	1sec~999sec or 1min~999min
Voltage	DC 24V adapter
Power	60W
Dimension	W.110 x D.156 x H.92mm
Net Weight	1kgs

Accessories



SBI-A



SBI-B



SBI-C



SBI-D



SBI-E

Specification

Cat#	Spec	Dia. of hole	Hole Bottom Shape	Block Dimension
SBI-A	φ10mm×15	10.5mm	Flat bottom	71x47x32mm
SBI-B	φ12mm×12	12.5mm	Flat bottom	71x47x32mm
SBI-C	φ15mm×6	15.5mm	Flat bottom	71x47x32mm
SBI-D	φ16mm×6	16.5mm	Flat bottom	71x47x32mm
SBI-E	φ9mm×18	9.5mm	Flat bottom	71x47x32mm