

# **Dual-Compartment FTIR Spectrometer** SFT-820



### **Discription**

SFT-820 FTIR spectrometer with two compartments for two channels independent operation, In-situ diffuse reflection and in-situ transmission cell synchronization, no necessary to replace attachments frequently

Configured to room temperature detector and low temperature LN MCT detector sychronization with a max. scan rate 60K

SFT-820 FTIR spectrometer with compact and rigid design to fit to multi-mode measurement of transmission, ATR, diffuse reflection, specular reflection. Dual sample compartment requires no frequent replacement can improve efficiency. It's widely applied to measure solid, liquid, and gas in the third party lab and in-situ characteristics of many categories of catalysts.

### **Features**

- 2 channels & 2 sample compartments for independent operation
- Easy to auto-switch channels on the software Auto adjust 6 scan speed with 2.5K-3.0K
- Software can auto-transfer in K-M format for convenient comparison with diffuse reflection spectra
- Save or import background spectra for comparing, reminder valid time function.
- Sample compartment is spacious for various bigger IR attachment.
- Optical path in good collimated, no necessary to replace large attachments with 2 compartment
- ZnSe beam splitter with little maintenance for optional

### **Specification**

Model	SFT-820		
Channels/Compartments	Auto-switch 2 channels, 2 compartments		
Spectral range	8000-350cm-1		
Spectral resolution	≤1cm-1		
Wavenumber precision	≤0.01cm-1		
Wavenumber accuracy	≤0.01cm-1		
Michelson interferometer	Michelson interferometer with wear free and reliability of 10 year guaranty, with		
	cube-corner mirror resist mechanical and temperature vibration		
Beam splitter	ZnSe, KBr		
Detector	LN MCT detector / DLATGS detector		
IR source	Long life vacuum cooling ceramic light source, 1550K		
Laser	Solid laser, 10 years warranty		
Software	Win10 software functions including FTIR spectra measure, spectra database		
	pretreatment, spectra comparison, standard peaks finding, user self-build library,		
	quantitative analysis, auto-deduct diamond/CO2 absorption peak, intelligent peak		
	finding warning, one-button test result evaluate, export report and print		
	Auto switch channels, configured to quick scan speed of 20K, 40K, 60K and		
	diffuse reflectance measure change to K-M spectra		

## **Application**

### **Chemical Reaction Kinetics of Catalysts**

- - Online catalysts at high temperature, high pressure or vacuum catalytic performance
- Catalytic reaction mechanics and process
- · Catalytic surface absorption activities and performances
- Catalytic characteristics of Acid/Alkali
- New catalysts experiment database
- Ingredients identification and structure analysis of catalysts sample

#### Multi-tasks measurements

Experimenters are always receive various samples for measurement, such as solid, liquid and gas and in order to make a different analysis, say transmission modules, ATR attachments. When it's necessary to replace the different FTIR attachments, SFT-820 can customize immovable attachments, auto-switch optical path at accuracy. Heating in-situ transmission cell

- High temperature/pressure in-situ diffuse reflection cell
- High temperature/vacuum in-situ diffuse reflection cell
- Low temperature/vacuum in-situ diffuse reflection cell
- Positive transitivity (paralleled incident light)
- Diffuse transmission (integrating sphere attachments)
- Reflectivity measure (reflective angle of 10°, 30°, 45°, 80°, and changed degree etc)
- ATR measurement (optional crystals: diamond, ZnSe, Ge)
- Solid, liquid, gas sample transmission characteristics

#### Pharm & Life Science

- Protein conformation and quantification
- Quantification for Active Pharmaceutical Ingredients and excipient in water solution

#### **Microorganism Identification**

· Characterization for the volatility and stability of medicine combined with TGA module

#### **Polymer and Chemical Products**

- Detection and Characterization for the volatility and decomposition combined with TGA module
- Monitoring reaction process in lab combined with MIR fiber probe module

#### Surface analysis

- Detection and Characterization for the Ultra-Thin film and mono-layer film
- Characterization for the erosion process

#### **Material Sciences**

- Detection of Emissivity of building materials
- · Evaluation for Optical material such as Infrared windows and mirrors

#### Semi-conductor Silicon Industry

- Different non-metal film measure
- Quality control medium carbon / oxygen impurity identification

#### **Soil Analysis**

- Soil fertility and organic evaluation
- Soil properties research

## **Attachment**

ltem	Model	Qty	Remarks
FTIR spectrometer	SFT-820	1 unit	Included
Room temperature detector	-	1 unit	Included
Desiccant kit	-	2 pcs	Included
Wires	-	1 unit	Included
computer	-	1 unit	Optional
In-situ diffuse reflection attachment, available in	-	1 unit	Optional
high temperature, low temperature, high pressure			
reaction cell			
In-situ transmission attachment	-	1 unit	Optional
(solid, liquid absorption, gas solid absorption			
Temperature control system	-	1 unit	Optional
Gas system	-	1 unit	Optional
Water cycle system	-	1 unit	Optional
Vacuum pump system	-	1 unit	Optional