STALWART

HD LCD Color Digital Camera SLC-450



Introduction

SLC-450 HD LCD Digital Camera is a brand new high performance and highly cost-effective, super reliable HD LCD camera which combines an full HD camera and a retina HD LCD screen. With the built-in software, the SLC-450 can be controlled by a mouse to take pictures, take videos and save to SD card.

Features

- · Control camera with mouse from USB port, no shaking.
- 11.6" retina HD LCD Screen, high definition and high quality color reproduction.
- 5.0MP still image capture and 1080P Video Recording.
- Save image and video to SD card.
- Also can be connected to PC and take picture, take video, do measurement and analyze images.
- Standard C-mount Interface for different microscopes.

Specification

| | Item | SLC-450 |
|-------------|--------------------|--------------------------------|
| HDMI Camera | Image Sensor | CMOS, Aptina MT9P031 |
| | Sensor Size | 1/2.5" |
| | Video Resolution | 1920 × 1080 |
| | Image Resolution | 2592 × 1944 |
| | Frame Rate | 1920 × 1080 15fps via USB2.0 |
| | | 1920 × 1080 15fps via HDMI |
| | Data Record | SD Card (4G) |
| | Video Record | 1080p 15fps @ SD Card |
| | | 1080p 15fps @ PC |
| | Scan Mode | Progressive |
| | Electronic Shutter | Electronic Rolling Shutter |
| | A/D conversion | 8 bit |
| | Color Depth | 24bit |
| | Sensitivity | 510mV |
| | Dynamic Range | 60dB |
| | S/N ratio | 40.5dB |
| | Exposure time | 0.001 sec ~ 10.0 sec |
| | Exposure | Auto/Manual |
| | White balance | Auto |
| | Settings | Gain,Gamma,Saturation,Contrast |
| | Built- in software | Cloud 1.0 version |
| | PC software | Capture2.0 |
| | Output model 1 | USB2.0 |

Specification

| | Output model 2 | HDMI |
|---------------|-------------------------|--|
| | System Compatible | Windows XP/Vista/Win 7/Win 8/10(32 and 64-bit), MAC OSX |
| | Optical port | C- Mount |
| | Power Supply | DC 12V /2A |
| | Operational Temperature | 0-60°C |
| | Humidity | 45%-85% |
| | Storage Temperature | -20-70°C |
| Retina Screen | Screen Size | 11.6 inch |
| | Aspect Ratio | 16:9 |
| | Display Resolution | 1920 × 1080 |
| | Display Type | IPS-Pro |
| | Brightness | 320cd/m2 |
| | Static Contrast Ratio | 1000:1 |
| | Input | 1*HDMI Port |
| | Power Supply | DC 12V /2A External Adapter |
| | Dimension | 282mm×180.5mm×15.3mm |
| | Net Weight | 600g |

Application

SLC-450 HDMI LCD digital camera is specifically developed for different microscopy applications. It can be widely used in medical diagnosis, industrial production and inspection, laboratory research and related microscopy field for image, video capture and analysis. It is mainly used for following areas:

- · Biological Teaching Digital Imaging
- Live Cell Imaging
- Surgical Microscopic Imaging
- Pathology
- Cytology
- Defect Analysis
- Semiconductor Inspection
- Navigation for Processed Imaging
- Industrial Optical HD Digital Imaging
- Astronomical Observation