STALWART

Multi-Tube Vortex Mixer SMT-25V



Introduction

Multi-tube Vortex Mixer can process 50 samples at the same time. Variety of accessories can be selected to meet the mixing needs with different specifications of test tubes.

Features

- Max capacity can process 50 samples at the same time to make the experiment more convenient and efficient.
- Microprocessor control, simplistic designed appearance, LED displays the speed and time.
- Friendly program designed, built-in short mix, timing operation, impluse and continuous modes. Operation stable and silent.
- A foam tube frame and tray pad configured at random. Various types of foam tube frames and pads to choose. tube frames and pads to choose.

Specification

Item	SMT-25V
Speed Range	500~2500rpm
Speed Accuracy	±1rpm
Shaking Orbit	4mm
Time Range	1s~9999min
Interval timing betweenimpulse	1~10s
Timing set for impuls working	1s~99min59S
Max Load	5kgs
Cover Plate Size	W.184 x L.311mm
Voltage	AC 100~230V, 50/60Hz
Power	60W
Fuse	250V, 1A, Ф5 x 20
Dimension	W.250 x D.426 x H.480mm
Net Weight	15kgs

Accessories







SMT-A

SMT-B

SMT-C







SMT-D SM-E SM-F







SMT-G SMT-H SMT-I

Specification

CAT#	Description	Number of holes	Dimention
SMT-A	Φ10mm foam tube frame	50	W.245 x D.132 x H.45mm
SMT-B	Φ12mm foam tube frame	50	W.245 x D.132 x H.45mm
SMT-C	Φ13mm foam tube frame	50	W.245 x D.132 x H.45mm
SMT-D	Φ16mm foam tube frame	50	W.245 x D.132 x H.45mm
	suit for 15ml tube		
SMT-E	Φ25mm foam tube frame	15	W.245 x D.132 x H.45mm
SMT-F	Φ29mm foam tube frame	15	W.245 x D.132 x H.45mm
	suit for 50ml tube		
SMT-G	Ф38mm foam tube frame	10	W.245 x D.132 x H.45mm
	suit for 100ml tube		
SMT-H	tray pad set (up pad & base pad)	1	W.305 x D.178.5 x H.25mm
SMT-I	acrylic tube frame Ф11mm	40	W.169 x D. 84 x H.41mm
	(suit for1.5/2.0ml tube)		