

STALWART

2-8°C, Pharmacy Refrigerator Spirit SPR-135S



Features

- Fit with famous brand compressor and condensor, better cool performance;
- HCFC-FREE refrigerant ensure environmental protection & safety.
- Air cooling, auto-defrost, temperature uniformity within 2°C

Humanized Operation Design

- Electrical heated glass door with key lock
- Multiple alarms: high and low temperature alarm, sensor failure alarm, power failure alarm, open alarm, remote alarm.
- Durable exterior and interior constructions, easy to clean;
- Standard castors for easy moving.
- Standard USB port, remote alarm contact and RS485 interface for monitor system.

Reliability

- High accuracy temperature controller with high sensitivity sensors, keep the temperature within 2~8°C, Display accuracy at 0.1°C.

Specification

	Model	SPR-135S
Technical Data	Cabinet Type	Under bench
	Capacity (L)	135
	Temperature Range (°C)	2~8
	Temperature Resolution(°C)	0.1
	Temperature ambient(°C)	16~32
	Temperature Control	Microprocessor
	Display	LED digital display
	Cooling Type	Forced-air Cooling
	Defrost Mode	Automatic
	Refrigerant	CFC-Free
	Noise (dB)	40
Functions	High/low Temperature Alarm	Y
	Power Failure Alarm	Y
	Sensor Error Alarm	Y
	Low Battery Alarm	Y
	Door Ajar Alarm	Y
	Ambient Temperature High Alarm	Y
	USB Failure Alarm	Y
	Remote Alarm Contact	Y

Specification

Electrical Data	Power (W)	147
	Power consumption(KWh/24h)	1.5
	Rated current (A)	0.54
Accessories	Voltage/Frequency(V/Hz)	220~240V 50/60Hz 110V 60Hz
	Door	Single Glass Door
	Door Lock	Y
	Caster	4
	Level Foot	2
	Shelf	2
	Remote Alarm Contact	Y
	Test Hole	Y
Dimensions	USB	Y
	Net/Gross Weight (kg)	41/44
	Internal Dimension (W/D/H, mm)	554×450×588
	External Dimension(W/D/H, mm)	650×625×810
	Packing Dimension(W/D/H, mm)	690×665×855
	Container Load (20'/40'/40'H)	54/120/120

Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Application can be found in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc