

STALWART

2-8°C, Pharmacy Refrigerator Classic SPR-360



Microprocessor control and digital display ensure inside temperature at 2-8°C and temperature resolution at 0.1°C

Environmentally friendly insulation material ensures low energy consumption.

Forced-air cooling
All models are equipped with fans to distribute the cooling air inside uniformly to ensure better temperature uniformity

Easy-to-maintain interior
Anti-corrosion and easy cleaning

Solid protection
Made from rust-proof, cold steel with white powder coating

Adjustable shelves
Adjustable shelf height to fill different drugs

Door lock
prevent unauthorized access

Automatic defrosting

Castors with brake, easy moving and lock



Features

- Accurate temperature control to maintain inner temperature at 2~8°C and increment at 0.1°C
- High-tech integrated sensors to display and control temperature
- Auto-defrost to remove moisture on cooling surface
- Remove able outdoor double seal design for better temperature maintain and energy saving

Reliability

- Microprocessor controlled forced-air cooling system
- Digital temperature display with 0.1°C resolution
- Double-layer glass door equipped with electrical heater(optional) to avoid condensation

Ergonomic Design

- Epoxy coated exterior: anti-bacteria and easy cleaning
- Adjustable shelves
- Caster with brake for easy moving and lock
- Interior LED light for easy observation
- Environment friendly refrigerants: CFC-free and HCFC-free

Safety

- Password protection prevent unauthorized temperature setting
- Lock to prevent unauthorized access
- Two alarm styles: buzzer and flash
- Start delay protection

Specification

	Model	SPR-360
Technical Data	Cabinet Type	Upright
	Capacity (L)	360
	Climate Class	10-32
	Cooling Type	Forced Air Cooling
	Defrost Mode	Automatic
	Refrigerant	CFC-Free
	Door	Single Glass Door
	Electrical Heater	Low-E
	Noise (dB)	43
	Temperature Range (°C)	2~8
Performance	Uniformity (°C)	±3°C
	Temperature Control	Microprocessor
Control	Display	LED
	Voltage/Frequency(V/Hz)	220~240V 50/60Hz
Electrical Data	Power (W)	136
	Net/Gross Weight (kg)	92/100
Dimensions	Internal Dimension (W/D/H, mm)	550×435×1420
	External Dimension(W/D/H, mm)	640×552×1880

Specification

Dimension	Packing Dimension(W/D/H, mm)	704×617×2000
	Container Load (20'/40'/40'H)	27/57/57
	High/low Temperature Alarm	Y
	Remote Alarm Contact	Optional
	Power Failure Alarm	Y
Functions	Sensor Error Alarm	Y
	Low Battery Alarm	Y
	Door Ajar Alarm	Y
	Door Lock	Y
	Caster	4
	Foot	Y
Accessories	Shelf/Chamber	5/-
	Test Hole	1/25mm
	Data logger	Optional
Others	Certificate	CE, ISO9001