

# STALWART

## 2-8°C, Pharmacy Refrigerator Classic SPR-656



## Features

- Accurate temperature control to maintain inner temperature at 2~8°C and increment at 0.1°C
- High-tech integrated sensors to display and control temperature
- Auto-defrost to remove moisture on cooling surface
- Remove able outdoor double seal design for better temperature maintain and energy saving

### Reliability

- Microprocessor controlled forced-air cooling system
- Digital temperature display with 0.1°C resolution
- Double-layer glass door equipped with electrical heater(optional) to avoid condensation

### Ergonomic Design

- Epoxy coated exterior: anti-bacteria and easy cleaning
- Adjustable shelves
- Caster with brake for easy moving and lock
- Interior LED light for easy observation
- Environment friendly refrigerants: CFC-free and HCFC-free

### Safety

- Password protection prevent unauthorized temperature setting
- Lock to prevent unauthorized access
- Two alarm styles: buzzer and flash
- Start delay protection

## Specification

	Model	SPR-656
Technical Data	Cabinet Type	Upright
	Capacity (L)	656
	Climate Class	10-32
	Cooling Type	Forced Air Cooling
	Defrost Mode	Automatic
	Refrigerant	CFC-Free
	Door	Side-by-side Glass Door
	Electrical Heater	Standard
	Noise (dB)	42
	Temperature Range (°C)	2~8
Performance	Uniformity (°C)	±3°C
	Temperature Control	Microprocessor
Control	Display	LED
	Voltage/Frequency(V/Hz)	220~240V 50/60Hz
Electrical Data	Power (W)	443
	Net/Gross Weight (kg)	158/188
Dimensions	Internal Dimension (W/D/H, mm)	1100×454×1325
	External Dimension(W/D/H, mm)	1220×642×1885

## Specification

Dimension	Packing Dimension(W/D/H, mm)	1290×695x1940
	Container Load (20'/40'/40'H)	13/27/27
	High/low Temperature Alarm	Y
	Remote Alarm Contact	Optional
	Power Failure Alarm	Y
Functions	Sensor Error Alarm	Y
	Low Battery Alarm	Y
	Door Ajar Alarm	Y
	Door Lock	Y
	Caster	4
	Foot	Y
Accessories	Shelf/Chamber	10/-
	Test Hole	1/25mm
	Data logger	Optional
Others	Certificate	CE, ISO9001