

STALWART

**-40°C Biomedical Freezer
STF-90B**



Introduction

Refrigeration System

Reliable compressor and fan, ensure fast cooling, energy-saving and long time running

The evaporator is intergrated with shelves and distribute in 6 compartments, ensures uniform temperature

Two reliable compressors control upper and lower compartment separately to ensure better cooling performance

Environment friendly refrigerant CFC-free and HFCF-free

Cabinet Construction

Powder coated steel exterior, Aluminum plate interior with round corner design easy to clean-up

Superior engineered frame for maximum rigidity

Self-closing door with magnetic closure

High thickness Non-CFC foamed insulation, energy saving

Doorlock prevents unauthorized access to the freezer

Low noise design creates a comfortable and quiet working environment

Independent compartments with ABS drawers are convenient to classify and store different samples

Features

- High-precision digital microprocessor temperature control system with digital
- LED temperature display 0.1°C accuracy.
- Temperature setting range is -20°C ~-40°C
- The digital display show freezer work condition and alarm code, easy to know freezer status
- Audibale and visible alarm system for safe storage:
- High temperature alarm, Low temperature alarm, Sensor failure alarm, Door ajar alarm, Power failure alarm, Lowbattery alarm, Hot condensor alarm;
- 3 sensors available for cooling, real time display and amabinet temperature display
- Build-in USB interface enable users to download the historical temperature data
- Optional for the remote alarm contact

Specification

| Model | | STF-90B |
|----------------|----------------------------|---------------------|
| Technical Data | Cabinet Type | Upright |
| | Capacity (L) | 90 |
| | Temperature Range (°C) | -20~ -40 |
| | Cooling Performance(°C) | -40 |
| | Temperature ambient(°C) | 10~32 |
| | Temperature Control | Microprocessor |
| | Display | LED digital display |
| | Cooling Type | Direct Cooling |
| | Defrost Mode | Manual |
| | Refrigerant | CFC-Free |
| | Noise (dB) | 40 |
| Functions | High/low Temperature Alarm | Y |
| | Power Failure Alarm | N |
| | Sensor Error Alarm | Y |
| | Low Battery Alarm | N |
| | Door Ajar Alarm | Y |

Specification

| | | |
|-----------------|--------------------------------|----------------------------|
| Electrical Data | Power (W) | 370 |
| | Power consumption(KWh/24h) | 1.69 |
| | Rated current (A) | 1.68 |
| | Voltage/Frequency(V/Hz) | 220~240V 50/60Hz 110V 60Hz |
| Accessories | Door | 1 foaming door |
| | Door Lock | Y |
| | Caster | 2 |
| | Foot | 2 |
| | Shelf/Drawer | 2/3 |
| | Test Hole | Y |
| | Remote Alarm Contact | N |
| | USB | N |
| Dimensions | Net/Gross Weight (kg) | 54/59 |
| | Internal Dimension (W/D/H, mm) | 500×485×532 |
| | External Dimension(W/D/H, mm) | 700×669×854 |
| | Packing Dimension(W/D/H, mm) | 745×712×927 |
| | Container Load (20'/40'/40'H) | 42/90/90 |